

STAR 13



GO EVERYWHERE

- > Smooth & precise driving
- > Comfort & agility
- > Indoor / outdoor rated (versatile)
- > Easy entry to the platform
- > Smart transportability and lifting

THE BEST VALUE FOR THE MONEY

- > Haulotte Activ'Energy Management takes care of your batteries
- > Easy access to components
- > Smart mast system
- > Minimal maintenance & downtime
- > Direct electric drive brushless AC motor
- > Haulotte Activ'Screen (onboard diagnostics)

VERTICAL MASTS

TECHNICAL DATA

STAR 13

| | |
|---------------------------------------|-------------------------------|
| Working height | 18 ft 6 in |
| Platform height | 12 ft 6 in |
| Horizontal outreach | N/A |
| Lift capacity | 507 lb (2 pers.) |
| Lift capacity - outside | 507 lb (1 pers.) |
| A Length | 4 ft 7 in |
| B Width | 2 ft 7 in |
| C Height - stowed | 5 ft 11 in |
| D Wheelbase | 3 ft 6 in |
| E Ground clearance | 2.36 in |
| Platform size | 2 ft 6 in x 4 ft 6 in |
| Platform size with extension (option) | 2 ft 6 in x 4 ft 6 in + 16 in |
| Drive speed | 0.5 - 2.8 mph |
| Turning radius - outside | 5 ft 7 in |
| Tilt alarm | 1.5 ° / 3 ° |
| Gradeability | 25 % |
| Driveable at full height up to | 12 ft 6 in |
| Tires | 13 x 5 |
| Batteries | 12 V - 105 Ah (C5) |
| Weight | 2,006 lb |

STANDARD EQUIPMENT

- > Haulotte Activ'Energy Management: Smart CAN charger
- > 24 V electric drive brushless AC motors
- > 2 x 12 V - 105 Ah batteries
- > Battery charge indicator
- > Haulotte Activ'Screen
- > Forklift pockets
- > Hoisting and lifting eyes
- > Saloon door entry gate
- > Mobile pothole protection
- > 2 Front steering wheels
- > 2 Rear drive wheels
- > Non-marking tires
- > Brake release
- > Hourmeter
- > Horn
- > Travel alarm
- > Emergency stop
- > Emergency hand pump
- > 2 control stations at platform and ground level
- > Mobile upper control box
- > 2 towing hooks
- > Walkable entry plinth
- > Overload sensor

OPTIONS AND ACCESSORIES

- > Haulotte Activ'Energy Management: automatic or manual battery waterfilling systems
- > Upper control box cover
- > Tool tray
- > 16 in platform extension deck (stowed height 5 ft 9.5 in) standard in US & Canada
- > Power to the platform
- > Ground-fault circuit interrupter 30 mA
- > Telematics ready
- > Biodegradable hydraulic oil
- > Cold weather hydraulic oil
- > Flashing beacon
- > Fluorescent tube caddy

