

# MEC 2632SE



<b>Make</b>	MEC
<b>Model</b>	2632SE
<b>Type</b>	Scissor Lifts

**How can we help?**

**(440) 291-0200**

## Description

2632SE - ELECTRIC SLIM SCISSOR LIFT

- Direct Electric Drive for Extended Duty Cycles and Faster Drive Speeds
- Standard Integrated Sheet Material Tray Allows 110 lbs. (50 kg) to be Stored and Lifted Outside the Platform
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Drivable at Full Height
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays

STANDARD FEATURES:

WORK AREA

- Standard Integrated Sheet Material Tray Designed and Approved by the Manufacturer
- Roll-Out Deck Extension with Incremental Locking Positions
- Standard Swing Gate
- Lanyard Attachments (4)

Text us!

## PERFORMANCE

- Direct Electric Drive
- Fully Proportional Drive and Lift Controls

## POWER

- 24v 225Ah DC Electric Power
- Battery Charge Indicator

## SERVICEABILITY

- Lubrication-Free Scissor Bearings
- Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray
- Logically Grouped Components and Numbered Wiring for Easy Reference

## SAFETY

- Dedicated Compartment Protects Electrical and Hydraulic Components
- Emergency Shut-Off at Platform and Lower Controls
- Non-Skid Metal Deck Construction
- Descent Alarm
- Drive Speed Interlock
- Multi-Axis Tilt Sensor
- Scissor Maintenance Lock
- Multiple Disc Brakes

## OTHER FEATURES

- Removable Upper Controls
- Voltage-Compensating Fully Automatic Battery Charger
- Fold-Down Guardrails
- Hour Meter
- Machine Tie Downs
- Non-Marking Tires
- All Motion Alarm
- Fork Lift Pocket
- U.S. Patent #8,678,135

## OPTIONAL FEATURES

- Flashing Beacon (Continuous)
- 900w Inverter
- PPSS - Proactive Platform Safety System
- Second Year Extended Warranty

Similar models may be shown in addition to the featured model. Equipment may be shown with options. Specifications are subject to change without prior notice.

# Specifications

**Chassis Width:** 32 in. | 81 cm

**Controls:** Proportional Drive && Lift Controls

**Drive Speed (Elevated):** 0.5 mph | 0.8 km/h

**Drive Speed (Stowed):** 2.5 mph | 4.0 km/h

**Gradeability:** 25%

**Ground Clearance (Elevated):** .7 in. | 2 cm

**Ground Clearance (Stowed):** 4 in. | 10 cm

**Guardrail Height:** 43.5 in. | 1.1 m

**Length-Stowed (Ladder Removed):** 89.5 in. | 2.3 m

**Length-Stowed (Overall):** 97 in. | 2.5 m

**Personnel Capacity:** 2

**Platform Height:** 26 ft. | 8 m

**Platform Length (Extended):** 124.5 in. | 3.2 m

**Platform Length (Retracted):** 89.5 in. | 2.27 m

**Platform Width:** 33 in. | 84 cm

**Power Source:** 24 v DC, 225Ah Battery Pack

**Raise/Lower Speed:** 42 s / 30 s

**Roll-Out Deck Capacity:** 250 lbs | 113 kg

**Roll-Out Deck Length:** 35 in. | 90 cm

**Sheet Tray Capacity:** 110 lbs | 50 kg

**Stowed Height (Platform Floor):** 48 in. | 1.2 m

**Stowed Height (Rails Folded):** 78 in. | 2 m

**Stowed Height (Top Guardrail):** 91 in. | 2.3 m

**Tires:** 15 x 5 in. | 38 x 13 cm

**Toeboard Height:** 6 in. | 15 cm

**Total Lift Capacity:** 500 lbs | 227 kg

**Weight\*\*:** 4,675 lbs. | 2,120 kg

**Wheelbase:** 74 in. | 1.9 m

**Working Height\*:** 32 ft. | 10 m