

**TABLE 1-1. SPECIFICATIONS AND FEATURES**

**Specifications**

	<b>SJB-40TB</b>	<b>SJB-45TB</b>	<b>SJB-60TB</b>	<b>SJB-65TB</b>
<b>WEIGHT</b>	12500#(5670kg)	14500#(6577kg)	23440#(10632kg)	26900#(12202kg)
<b>WORK HEIGHT (Nominal)</b>	46'(14.0m)	51'(15.5m)	66'(20.1m)	71'(211.6m)
<b>RAISED PLATFORM HEIGHT (Nominal)</b>	40'(12.2m)	45'(13.7m)	60'(18.3m)	65'(19.8m)
<b>HORIZONTAL REACH (CL rotation)</b>	33' 0"(10.1m)	38' 0"(11.9m)	52' 0"(15.8m)	57' 0"(17.4)
<b>STOWED HEIGHT</b>	7' 8"(2.3m)	7' 8"(2.3m)	8' 6"(2.6m)	8' 6"(2.6m)
<b>STOWED LENGTH</b>	25' 5"(7.75m)	22' 5"(6.83m)	28' 10"(8.8m)	26' 5"(8.1m)
<b>OVERALL WIDTH</b>	8' (2.4m)	8' (2.4m)	8' 0"(2.44m)	8' 0"(2.44m)
<b>PLATFORM CAPACITY (Unrestricted)</b>	600#(272kg)	500#(227kg)	600#(272kg)	500#(227kg)
<b>PLATFORM SIZE</b>	30"x72"(.76mx1.83m)			
<b>ELECTRICAL SYSTEM</b>	12 Volts DC			
<b>GRADABILITY</b>	30%			
<b>TURRET ROTATION</b>	Continuous			
<b>TIRE SIZE</b>	12x16.5	12x16.5	15x19.5	15x19.5

**Features**

**STANDARD EQUIPMENT**

Variable Speed Drive and Function Controls  
 Continuous Drive and Steer Directional Sensing  
 12 Volt DC Emergency Power  
 Engine Anti-restart Protection  
 Spring-Applied Hyd-Released Parking Brakes  
 ANSI and CSA Standards Compliance  
 110V Outlet on Platform with GFI  
 Ford LRG 425-EFI (2.5L) Gasoline Engine

**OPTIONAL EQUIPMENT**

Kubota Diesel Engine  
 Dual Fuel (Gas/Propane)  
 Operator Horn  
 All Function Motion Alarm  
 Travel Alarm  
 Descent Alarm  
 Flashing Amber Light  
 Platform or Chassis Work Lights  
 Spring-Loaded Half Gate  
 Spring-Loaded Full Gate  
 Air or Hydraulic Line to Platform  
 Cold Weather Start  
 High Flotation Tires  
 Foam Filled Tires  
 Four Wheel Drive  
 30"x96" Platform