

 **TEREX AERIALS**
OPERATOR'S MANUAL

Specifications

*Working Height	31 ft. (9.45 m)
Platform Height	25 ft. (7.62 m)
Stowed Height:	
Without Rails	51 in. (1.29 m)
With Rails	93 in. (2.36 m)
Platform Capacity (Evenly Distributed):	
With Standard Deck	1,500 lbs. (680 kg)
With Roll-Out Deck (Optional)	1,250 lbs. (560 kg)
Platform Dimensions:	
With Standard Deck	64 in. x 124 in. (1.63 m x 3.15 m)
Guard Rail Height	42 in. (1.07 m)
Toe Board Height	6 in. (1.5 cm)
Roll-Out Deck (Optional)	3 ft. (0.91 m)
Length	128 in. (3.25 m)
Width	75 in. (1.91 m)
Wheelbase	95 in. (2.41 m)
Wheel Track	63 in. (1.60 m)
Inside Turning Radius	11 ft. (3.43 m)
Outside Turning Radius	18 ft. (5.49 m)

 **WARNING**

*** CLEARANCE MUST BE ALLOWED FOR BODY PARTS OF PERSONNEL IN PLATFORM AT THIS AND ALL OTHER WORK HEIGHTS.**

 **TEREX AERIALS**
OPERATOR'S MANUAL

Maintenance

Hydraulic Fluid (Continued)

 **CAUTION**

Any hydraulic fluid used in the hydraulic system of this aerial lift must meet or exceed the specifications of the fluid initially supplied.

At the next complete hydraulic fluid change, the fluid may be switched to your preferred brand.

 **WARNING**

HYDRAULIC FLUID UNDER PRESSURE IS HOT, CAN PENETRATE AND BURN THE SKIN, DAMAGE EYES, AND MAY CAUSE SERIOUS INJURY, BLINDNESS, AND EVEN DEATH. CORRECT LEAKS IMMEDIATELY.

FLUID LEAKS UNDER PRESSURE MAY NOT ALWAYS BE VISIBLE.

IF A MINERAL-BASED HYDRAULIC FLUID HAS PENETRATED THE SKIN, IT MUST BE MEDICALLY TREATED, WITHIN A FEW HOURS, BY A DOCTOR FAMILIAR WITH THIS TYPE OF INJURY.

ALWAYS CLEAN UP FUEL, HYDRAULIC FLUIDS AND LUBRICATING OILS SPILLED ON THE MACHINE. SPILLS CAN CAUSE FALLS, AND ARE A SERIOUS FIRE HAZARD.