

 **TEREX AERIALS**
OPERATOR'S MANUAL

Specifications

Machine Specifications	Model TS26	Model TS26W
* Maximum Working Height.....	32 ft. (9.75 m)	32 ft. (9.75 m)
Maximum Platform Height.....	26 ft. (7.92 m)	26 ft. (7.92 m)
Minimum Platform Height (Ground to Platform)	45 in. (1.14 m)	45 in. (1.14 m)
Stowed Height (With Platform Rails Up)	85 in. (2.16 m)	85 in. (2.16 m)
 Platform Capacity (Evenly Distributed, Includes Occupants):		
On Main Deck	1,000 lbs. (454 kg)	1,300 lbs. (590 kg)
On Extendable Platform	300 lbs. (136 kg)	300 lbs. (136 kg)
Rated Number of Occupants in Platform	3	3
Platform:		
Outside Dimensions	48 in. x 98 in. (1.22 m x 2.49 m)	52 in. x 98 in. (1.32 m x 2.49 m)
Guard Rail Height (Fixed).....	39.5 in. (1.0 m)	39.5 in. (1.0 m)
Guard Rail Height (Folded Down)	26 in. (0.66 m)	26 in. (0.66 m)
Toe Board Height	6 in. (1.5 cm)	6 in. (1.5 cm)
Extendable Platform	3 ft. (0.91 m) forward	3 ft. (0.91 m) forward
 Machine Length (Overall)	 8 ft. 2 in. (98 in.) (2.49 m)	 8 ft. 2 in. (98 in.) (2.49 m)
Machine Width (Overall)	48 in. (1.22 m)	54 in. (1.37 m)
Wheelbase	6 ft. 3 in. (75 in.) (1.91 m)	6 ft. 3 in. (75 in.) (1.91 m)
Wheel Track	45 in. (1.14 m)	49 in. (1.24 m)
Inside Turning Radius.....	4 ft. 7 in. (1.40 m)	4 ft. 5 in. (1.35 m)
Ground Clearance	4 in. (10.16 cm)	4 in. (10.16 cm)
Shipping Weight (Approx.)	4,200 lbs. (1905 kg)	4,400 lbs. (1996 kg)

 **WARNING**

*** CLEARANCE MUST BE ALLOWED FOR BODY PARTS OF PERSONNEL IN PLATFORM AT THIS AND ALL OTHER WORK HEIGHTS.**