

TEREX AERIALS OPERATOR'S MANUAL

Specifications

Machine Specifications

Model TS37RT

* Working Height	43 ft. (13.11 m)
Maximum Platform Height	37 ft. (11.28 m)
Stowed Height:	
With Platform Rails Installed	111.5 in. (2.83 m)
With Platform Rails Removed	69.5 in. (1.77 m)
Platform Capacity (Evenly Distributed):	
With Standard Deck	1,500 lbs. (680 kg)
With Traversing or Roll-Out Deck (Option)	1,250 lbs. (560 kg)
Rated Number of Occupants in Platform	4
Platform Dimensions:	
With Standard Deck	76 in. x 160 in. (1.93 m x 4.1 m)
Guard Rail Height (Fixed)	42 in. (1.07 m)
Guard Rail Height (Folded, Optional)	21.25 in. (0.54 m)
Toe Board Height	6 in. (1.5 cm)
Roll-Out Deck	3 ft. (0.91 m) forward
Traversing Deck (Optional)	4 ft. (1.22 m) forward
Machine Length (Overall)	14 ft. (4.27 m)
Machine Width (Overall)	8 ft. 3 in. (2.52 m)
Wheelbase	9 ft. 9 in. (2.97 m)
Wheel Track	7 ft. 1 in. (2.16 m)
Inside Turning Radius	13 ft. (3.96 m)
Outside Turning Radius	22 ft. (6.71 m)
Ground Clearance	10 in. (25.4 cm)
Shipping Weight (Approx.)	7,885 lbs. (3577 kg)

WARNING

*** CLEARANCE MUST BE ALLOWED FOR BODY PARTS OF PERSONNEL IN PLATFORM AT THIS AND ALL OTHER WORK HEIGHTS.**