

ELECTRIC SERIES SCISSOR LIFTS

1932ME

Compliant with ANSI/CSA standards

PRODUCT HIGHLIGHTS

Outstanding Performance

- Meets indoor & outdoor requirements
- Electric drive system with integrated leak containment ensures extended battery runtime and is ideal for environmentally sensitive job sites
- Compact footprint with standard folding guardrails allows seamless access through standard doorways

Low Maintenance Cost

- Durable structural design with side-opening doors for long machine life and serviceability
- Onboard fault diagnostics with integrated error codes and resolution guidance, no external analyzer required
- Shares many common parts with other Sinoboom scissors for simplified maintenance
- Bumper protection helps prevent scratches and damage
- AGM battery is included as a standard feature

Easy Operation

- High platform capacity and fast lift/lower speed help complete tasks more efficiently
- Optimized for transport with dual-access forklift pockets for flexible loading options



Standard Features		
Maintenance-free battery	Fully proportional controls	Non-marking tires
Automatic braking system	Emergency lowering system	Emergency stop
Fault diagnosis system	Tilt protection system	Flashing beacon
Forklift pocket and lifting eyes	Electrophoresic paint	Horn and buzzer
Automatic pothole guard system	Manual storage box	Foldable platform rails
Bumper rails	Drivable at full height	Leak containment
AC power to the platform	2WD × 2WS	Weighing system
Options & Accessories		
Telematics	Perimeter lighting	Function enable foot pedal
Anti-collision system		

SINOBOOM™
— NORTH AMERICA

PARTNERS IN ACCESS™

SINOBOOM.US | INFO@SINOBOOM.US
105 W RILEY ROAD, HOUSTON TX 77047

ELECTRIC SERIES SCISSOR LIFTS

1932ME

Compliant with ANSI/CSA standards

Model	1932ME
Dimensions	
Max Working Height (Indoor/Outdoor)	25' (7.6 m)
A Max Platform Height (Indoor/Outdoor)	19' (5.8 m)
B Platform Extension	3' (0.9 m)
C Length-Stowed	5'11" (1.8 m)
D Machine Width	2'8" (0.81 m)
E Height-Stowed (Rails Folded)	6'2" (1.88 m)
E Height-stowed (Rails Unfolded)	7' (2.14 m)
F Wheelbase	4'4" (1.33 m)
Ground Clearance (Pothole Guard Stowed)	3" (75 mm)
Ground Clearance (Pothole Guard Deployed)	0.95" (24 mm)
Platform Size (L×W×H)	5'5"×2'6"×3'7" (1.64 m×0.76 m×1.1 m)
Performance	
Platform Capacity	507 lbs (230 kg)
Extension Deck Capacity	265 lbs (120 kg)
Max Platform Occupants	2 Persons (Indoor) 1 Person (Outdoor)
Drive Speed (Stowed)	0 ~ 2.5 mph (0 ~ 4 km/h)
Drive Speed (Raised)	0 ~ 0.5 mph (0 ~ 0.8 km/h)
Lift Time (Unloaded)	15 s~20 s
Lower Time (Unloaded)	25 s~30 s
Gradeability	25%
Max Allowable Inclination(Front-to-Back/Side-to-Side)	3° /1.5°
Turning Radius (Inside/Outside)	0 /4'11" (0 m/1.49 m)
Tire Spec/Type	12.7×4" (323×100mm)/solid
Power	
Batteries	4×6 V, 220 Ah
Power Source	24V DC
Drive Mode	Motor, Front Wheel
Charger Input	100 ~ 240V AC
Charger Output	30 A
Hydraulic Tank Capacity	1.85 gal (US)(7L)
Weight	
Weight (Indoor/Outdoor)	3,473 lbs (1,575 kg)
Standards Compliance	ANSI/CSA

